

AXIAL AC FANS

8025

:80x80x25mm



Model	P/N	Bearing	Rating Voltage (VAC)	Power Current (AMP)	Power Consumption (WATTS)	Speed (RPM)	Air Flow (CFM)	Static Pressure (Inch-H ₂ O)	Noise (dBA)	Weight (g)
SF11580AT	1082HSL	⊗	115	0.12/0.10	12/11	2300/2750	17/21	0.12/0.18	29/33	260
SF11580AT	1082HBL	○	115	0.12/0.10	12/11	2450/2900	18/22	0.13/0.19	30/34.5	260
SF23080AT	2082HSL	⊗	220/240	0.07/0.07	14/13.5	2300/2750	17/21	0.12/0.18	29/33	260
SF23080AT	2082HBL	○	220/240	0.07/0.07	14/13.5	2450/2900	18/22	0.13/0.19	30/34.5	260
SF23080AT	2082MBL	○	220/240	0.07/0.07	15/14	2000/2400	12/15	0.11/0.16	24/28	260

8038

:80x80x38mm



Model	P/N	Bearing	(VAC)	(AMP)	(WATTS)	(RPM)	(CFM)	(Inch-H ₂ O)	(dBA)	(g)
SF11580A	1083HSL	⊗	115	0.15/0.13	14/12	2300/2750	23/30	0.12/0.18	31/35	340
SF11580A	1083MSL	⊗	115	0.11/0.10	11/10	2300/2700	18/23	0.12/0.18	31/35	340
SF11580A	1083HBL	○	115	0.15/0.13	14/12	2400/2850	24/31	0.13/0.19	32/36.5	340
SF11580A	1083MBL	○	115	0.11/0.10	11/10	2400/2800	19/24	0.13/0.19	32/36.5	340
SF23080A	2083HSL	⊗	220/240	0.07/0.06	14/13.5	2300/2750	23/30	0.12/0.18	31/35	340
SF23080A	2083HBL	○	220/240	0.07/0.06	14/13.5	2400/2850	24/31	0.13/0.19	32/36.5	340

9225

:92x92x25mm



Model	P/N	Bearing	(VAC)	(AMP)	(WATTS)	(RPM)	(CFM)	(Inch-H ₂ O)	(dBA)	(g)
SF11592A	1092HSL	⊗	115	0.12/0.11	13.0/12	2250/2750	29/36	0.12/0.18	36/39	280
SF11592A	1092HST	⊗	115	0.12/0.11	13.0/12	2250/2750	29/36	0.12/0.18	36/39	280
SF11592A	1092HBL	○	115	0.12/0.11	13.0/12	2350/2850	30/37	0.13/0.19	37/40	280
SF11592A	1092HBT	○	115	0.12/0.11	13.0/12	2350/2850	30/37	0.13/0.19	37/40	280
SF23092A	2092MBL	○	220/240	0.07/0.07	15.0/14	2200/2700	28/35	0.12/0.18	35/38	280
SF23092A	2092MBT	○	220/240	0.07/0.07	15.0/14	2200/2700	28/35	0.12/0.18	35/38	280
SF23092A	2092HSL	⊗	220/240	0.07/0.06	14.5/14	2250/2750	29/36	0.12/0.18	36/39	280
SF23092A	2092HST	⊗	220/240	0.07/0.06	14.5/14	2250/2750	29/36	0.12/0.18	36/39	280
SF23092A	2092HBL	○	220/240	0.07/0.06	14.5/14	2350/2850	30/37	0.13/0.19	37/40	280
SF23092A	2092HBT	○	220/240	0.07/0.06	14.5/14	2350/2850	30/37	0.13/0.19	37/40	280

12025

:120x120x25mm



Model	P/N	Bearing	(VAC)	(AMP)	(WATTS)	(RPM)	(CFM)	(Inch-H ₂ O)	(dBA)	(g)
SP103AT	1122LSL	⊗	115	0.14/0.13	14/13	1600/1800	46/53	0.11/0.12	35/38	330
SP101AT	1122HSL	⊗	115	0.19/0.18	19/18	2000/2200	64/77	0.13/0.15	43/45	330
SP103AT	1122LST	⊗	115	0.14/0.13	14/13	1600/1800	46/53	0.11/0.12	35/38	330
SP101AT	1122HST	⊗	115	0.19/0.18	19/18	2000/2200	64/77	0.13/0.15	43/45	330
SP103AT	1122LBL	○	115	0.14/0.13	14/13	1700/1900	47/54	0.12/0.13	37/40	330
SP101AT	1122HBL	○	115	0.19/0.18	19/18	2150/2300	66/78	0.14/0.16	44/46	330
SP103AT	1122LBT	○	115	0.14/0.13	14/13	1700/1900	47/54	0.12/0.13	37/40	330
SP101AT	1122HBT	○	115	0.09/0.09	19/18	2150/2300	66/78	0.14/0.16	44/46	330
DP203AT	2122LSL	⊗	220/240	0.07/0.07	14/13	1600/1800	46/53	0.11/0.12	35/38	330
DP201AT	2122HSL	⊗	220/240	0.09/0.09	19/18	2000/2200	64/77	0.13/0.15	43/45	330
DP203AT	2122LST	⊗	220/240	0.07/0.07	14/13	1600/1800	46/53	0.11/0.12	35/38	330
DP201AT	2122HST	⊗	220/240	0.09/0.09	19/18	2000/2200	64/77	0.13/0.15	43/45	330
DP203AT	2122LBL	○	220/240	0.07/0.07	14/13	1700/1900	47/54	0.12/0.13	37/40	330
DP201AT	2122HBL	○	220/240	0.09/0.09	19/18	2150/2300	66/78	0.14/0.16	44/46	330
DP203AT	2122LBT	○	220/240	0.07/0.07	14/13	1700/1900	47/54	0.12/0.13	37/40	330
DP201AT	2122HBT	○	220/240	0.09/0.09	19/18	2150/2300	66/78	0.14/0.16	44/46	330

*Specifications subject to change without notice

METAL FINGER GUARD






FG-08 For 80mm Fan

FG-09 For 92mm Fan

FG-12 For 120mm Fan

FG-17 For 172mm Fan

FG-25 For 254mm Fan



AXIAL AC Fans

12038

:120x120x38mm



Model	P/N	Bearing	Rating Voltage (VAC)	Power Current (AMP)	Power Consumption (WATTS)	Speed (RPM)	Air Flow (CFM)	Static Pressure (Inch-H ₂ O)	Noise (dBA)	Weight (g)
SP103A	1123LSL	⊙	115	0.13/0.11	11/11	2000/2200	70/76	0.08/0.12	36/38	550
SP101A	1123HSL	⊙	115	0.21/0.18	20/18	2550/2900	85/105	0.25/0.30	43/48	550
SP100A	1123XSL	⊙	115	0.26/0.24	22/20	2700/3100	95/115	0.33/0.38	44/49	550
SP103A	1123LST	⊙	115	0.13/0.11	11/11	2000/2200	70/76	0.08/0.12	36/38	550
SP101A	1123HST	⊙	115	0.21/0.18	20/18	2550/2900	85/105	0.25/0.30	43/48	550
SP100A	1123XST	⊙	115	0.26/0.24	22/20	2700/3100	95/115	0.33/0.38	44/49	550
SP103A	1123LBL	○	115	0.13/0.11	11/11	2150/2300	72/78	0.09/0.13	37/39	550
SP101A	1123HBL	○	115	0.21/0.18	20/18	2750/3050	87/107	0.26/0.32	45/50	550
SP100A	1123XBL	○	115	0.26/0.24	22/20	2850/3150	97/117	0.34/0.39	45/50	550
SP103A	1123LBT	○	115	0.13/0.11	11/11	2150/2300	72/78	0.09/0.13	37/39	550
SP101A	1123HBT	○	115	0.21/0.18	20/18	2750/3050	87/107	0.26/0.32	45/50	550
SP100A	1123XBT	○	115	0.26/0.24	22/20	2850/3150	97/117	0.34/0.39	45/50	550
SP102A	1123MBL	○	115	0.17/0.16	16/15	2500/2700	80/88	0.15/0.22	35/40	550
SP102A	1123MBT	○	115	0.17/0.16	16/15	2500/2700	80/88	0.15/0.22	35/40	550
DP203A	2123LSL	⊙	220/240	0.06/0.05	11/10	2000/1800	70/63	0.08/0.07	36/32	550
DP201A	2123HSL	⊙	220/240	0.125/0.11	20/19	2550/2900	85/105	0.25/0.30	43/48	550
DP200A	2123XSL	⊙	220/240	0.14/0.12	22/21	2700/3100	95/115	0.33/0.38	44/49	543
DP203A	2123LST	⊙	220/240	0.06/0.05	11/10	2000/1800	70/63	0.08/0.07	36/32	550
DP201A	2123HST	⊙	220/240	0.125/0.11	20/19	2550/2900	85/105	0.25/0.30	43/48	550
DP200A	2123XST	⊙	220/240	0.14/0.12	22/21	2700/3100	95/115	0.33/0.38	44/49	543
DP203A	2123LBL	○	220/240	0.08/0.06	10/10	2150/2300	72/78	0.09/0.13	37/39	550
DP201A	2123HBL	○	220/240	0.125/0.11	20/19	2750/3050	87/107	0.26/0.32	45/50	550
DP200A	2123XBL	○	220/240	0.14/0.12	22/21	2850/3150	97/117	0.34/0.39	45/50	550
DP203A	2123LBT	○	220/240	0.08/0.06	10/10	2150/2300	72/78	0.09/0.13	37/39	550
DP201A	2123HBT	○	220/240	0.125/0.11	20/19	2750/3050	87/107	0.26/0.32	45/50	550
DP200A	2123XBT	○	220/240	0.14/0.12	22/21	2850/3150	97/117	0.34/0.39	45/50	550

:172x150x51mm



Model	P/N	Bearing	(VAC)	(AMP)	(WATTS)	(RPM)	(CFM)	(Inch-H ₂ O)	(dBA)	(g)
A1175-HBT	T	○	115	0.60/0.55	49/45	2650/2950	180/200	0.48/0.48	52/55	942
A1175-HBL	T	○	115	0.60/0.55	49/45	2650/2950	180/200	0.48/0.48	52/55	942
A1175-HBT	TC	○	115	0.24/0.26	27/29	2800/3200	202/239	0.62/0.69	51/58	908
A1175-HBL	TC	○	115	0.24/0.26	27/29	2800/3200	202/239	0.62/0.69	51/58	908
A2175-HBL	T	○	220/240	0.27/0.25	43/40	2600/2800	178/192	0.38/0.44	52/54	942
A2175-HBT	T	○	220/240	0.27/0.25	43/40	2600/2800	178/192	0.38/0.44	52/54	942
A2175-HBL	TC	○	220/240	0.12/0.15	26/31	2800/3200	202/239	0.62/0.69	51/58	908
A2175-HBT	TC	○	220/240	0.12/0.15	26/31	2800/3200	202/239	0.62/0.69	51/58	908

:254x90mm




Model	P/N	Bearing	(VAC)	(AMP)	(WATTS)	(RPM)	(CFM)	(Inch-H ₂ O)	(dBA)	(g)
A1259-HBL	TC	○	115	0.50/0.60	57/68	2150/2000	867/806	0.46/0.37	57/56	2000
A1259-MBL	TC	○	115	0.25/0.25	25/28	1400/1600	600/665	0.27/0.36	50/52	2000
A1259-MBT	TC	○	115	0.25/0.25	25/28	1400/1600	600/665	0.27/0.36	50/52	2000
A2259-HBL	TC	○	220/240	0.28/0.34	64/78	2300/2200	915/886	0.49/0.41	59/57.5	2000
A2259-MBL	TC	○	220/240	0.15/0.13	30/30	1400/1650	600/665	0.27/0.36	48/52	2000
A2259-MBT	TC	○	220/240	0.15/0.13	30/30	1400/1650	600/665	0.27/0.36	48/52	2000


*Specifications subject to change without notice

PLASTIC GUARD


PB-08 For 80mm Fan



PB-09 For 92mm Fan




PB-12 For 120mm Fan



AC CORD

Power cord with straight connector



A2-03	300mm Length
A2-06	600mm Length
A2-10	1000mm Length
A2-20	2000mm Length